

# INVERTER PLASMA CUTTING MACHINE WP120A



MODEL	WP120A
RATED INPUT VOLTAGE ( V )	3x380 ±10% 50/60hZ
RATED INPUT POWER ( kva )	25,7
RATED INPUT CURRENT ( A )	39
RATED OUTPUT VOLTAGE ( V )	128
RANGE OF WELDING CURRENT ( A )	30-120
OPEN LOAD VOLTAGE ( V )	345
RATED DUTY CYCLE	60%
FEED GAS PRESSURE ( Mpa )	0,45-0,55
OPTIMUM CUTTING THICKNESS (mm)	35
MAX CUTTING THICKNESS (mm)	1,0 - 30,0
GAS FLOW SPEED ( L/min )	250
DIMENSION (LxHxW) (mm)	576x297x557
WEIGHT (Kg)	43,5

STANDARD AREAS OF USE	
CONNECTED PRIMARY CABLE	1 Pcs
PLASMA TORCH	1 Pcs
QUICK PLUG	1 Unit

 **CV. ANUGRAH DUTA NIAGA**

Jalan Arief Rachman Hakim 51, Ruko 21 Blok D-1 Klampis, Sukolilo, Surabaya

Telp : ( 031 ) 5990089 ; 5997259

Fax : 031 -5966099

Web Site : [www.adnsby.co.id](http://www.adnsby.co.id)

Email : [adn\\_office@yahoo.com](mailto:adn_office@yahoo.com)