

Weiro SAW Inverter MZ-1250D & MZ-3C SAW Trolley



MODEL		MZ 1250D
Input Voltage		3 x 380V $\pm$ 10% ; 50/60 Hz
Input Power Capacity (kVA)		60
Open Circuit Voltage (V)		75 - 85
Rated Output Voltage (V)		44
Welding Current Range (A)		100 - 1200
Duty Cycle		60%
Welding Wire Diameter		3.0 / 4.0 / 5.0 / 6.0
Dimension		590 x 490 x 1250
Weight		135
STANDARD ACCESSORIES		
Rail		2 Pcs @ 1m
Control Cable		1 Pcs (15m)
Welding Cable		1 Pcs (15m)
Ground Cable		1 Pcs (3m)

MODEL		MZ-3C
Sending Wire Speed (cm/min)		20 - 200
Sending Wire Mode		Changing Speed / Constant Speed
Welding Speed (cm/min)		15 - 150
Welding Head Adjust Range (Plumb) (mm)		95
Welding Head Adjust Range (Horizontal) (mm)		35
STUD Up/Down Range (mm)		100
Welding Head Deflection Angle (Left-Right)		45°
Welding Head Deflection Angle (Front-Rear)		60°
Dimension (mm)		920 x 455 x 820
Weight (kg)		52

 **CV. ANUGRAH DUTA NIAGA**

Jalan Arief Rachman Hakim 51, Ruko 21 Blok D-1 Klampis, Sukolilo, Surabaya

Telp : (031) 5990089 ; 5997259

Fax : (031) 5966099

WA : 0851 0199 2232 ; 0877 2596 6999

Website : adnsby.co.id

Email : adn_office@yahoo.com