

Weiro Inverter Plasma Cutting WP-40A

Input : Single Phase 230V
Process : CUT

Features And Benefits :

- Portable, high efficient IGBT Inverter
- Fast Dynamic response and arc Concentration, Smooth cutting edge
- Built-in relive valve, fewer installation work
- HF contact arc ignition
- High Duty Cycle, Up to 100% under room temperature
- 2/4T trigger mode for long/short seam
- Additional smart stuck fan protection



Recommended Applications :

- Machine manufacturing and maintenance
- Automobile
- Chemical machinery
- Pressure vessel
- Metal processing



MODEL	WP 40A
Input Voltage	1 x 230V \pm 10% ; 50/60 Hz
Input Power Capacity (kVA)	5.2
Output Current Range (A)	15 - 40
Duty Cycle	60%
Peak Open Circuit Voltage (V)	285
Max Cutting Thickness (mm)	12
Quality Cutting Thickness (mm)	Mild Steel: 10 Stainless Steel: 8
Air Ignition	HF Touched
Air Pressure (mPa)	0.2 - 0.4
Flow Rate (L/min)	250
Air Post-Flow Time (sec)	30
Cooling Type	Forced Air
Protection / Insulation Class	IP23S / F
Dimension (LxWxH)(mm)	391 x 155 x 298
Weight (kg)	9
Cos ϕ	0.98
Efficiency	\geq 80%
STANDARD ACCESSORIES	
Ground Clamp	1 Pcs (2m)
Plasma Torch	1 Pcs (4m)

ADN CV. ANUGRAH DUTA NIAGA

Jalan Arief Rachman Hakim 51, Ruko 21 Blok D-1 Klampis, Sukolilo, Surabaya

Telp : (031) 5990089 ; 5997259

Fax : (031) 5966099

WA : 0851 0199 2232 ; 0877 2596 6999

Website : adnsby.co.id

Email : adn_office@yahoo.com